

FleetPulseGO

Track

Go the distance with **FleetPulseGO Track**, the low-cost, ultra-compact asset tracker for fleet visibility and asset recovery insights. Track requires no maintenance or hardwiring, withstands extreme temperatures, and features up to seven years of battery life—without replacements. Combined with its design for quick and discreet placement, Track is truly the ultimate “set it and forget it” for fleet protection.



Key Highlights

- Up to 7-year of battery life for extended, worry-free tracking and recovery
- Ultra-compact design for discreet placement anywhere
- No hardwiring and zero maintenance required
- Customizable, automated check-ins
- Expansive, accurate cellular and GNSS coverage
- Install indicators provide deployment-ready confirmation
- 3-axis accelerometer, motion / no motion, and impact detection
- Configurable modes based on the movement or recovery of various assets

Mechanical

| | |
|--------------------|---|
| Dimensions..... | 2.80" x 2.80" x 1.97" (71mm x 71mm x 50mm) |
| Weight | 8 oz. (227g) Typical |
| Case Material..... | Plastic (black) |
| Mounting | 5 x Magnets (included in base), 2 x Zip Ties (4mm max width) not included |

Electrical

| | |
|--------------------|--|
| DC Power | DC 3.6V |
| Power Source | Internal 19Ah Lithium Thionyl Chloride Battery (Li-SOCL2) |
| Reporting..... | Inventory Management Mode: Max seven per day Normal Operating Mode: Eight updates per day |

Away Mode: One update per day (Device transitions to this mode to conserve battery if there is 48 hours of no motion, and returns to Normal Mode with motion detection)

Recovery Mode: No vehicle motion: one per day. Vehicle in motion: one every 5 minutes while vehicle is in motion.

Reporting intervals are configurable. Contact FleetPulse for details.

Environmental

| | |
|------------------------------|---|
| Push Button..... | Wakeup, Report or Return to Shipping Mode |
| Operational Temperature..... | -30°C to +60°C (-22°F to +140°F) |
| IP Rating..... | IP67 |

Communications

| | |
|----------------|--|
| Cellular | Comm. Interfaces: 4G Cat M1 Supporting Regions: NA, EU 4G LTE Bands: NA: 2, 4, 12 Power Class: 3 (23 dBm) SMS Support: MT/MNO |
|----------------|--|

Positioning

| | |
|-----------|--|
| GNSS..... | Tracking Sensitivity: -160dBm Hot Start: 3 seconds (open sky) Cold Start: 45s (open sky) Accuracy: <2.5 m (open sky) AGPS: Assistance Data Download for GPS |
|-----------|--|

Certifications

| | |
|----------------|----------------|
| Cellular | FCC, IC, PTCRB |
|----------------|----------------|